VIDEO BOOSTER

Bei diesem Video Booster handelt es sich um einen Video Signalverstärker, welcher das Videosignal einer PC – Grafikkarte bis auf eine Entfernung von 65m überträgt.

- Bildwiederholfrequenz 250 MHz.
- Videosignalverstärkung bis zu einer Distanz von 65m.
- Unterstützung DDC, DDC2, DDC2B.
- Kaskadierbar.
- VGA kompatibles Ausgangssignal.

Video Eingang (Video In)	1 x HD-15 Stecker
Video Ausgang (Video Out)	1 x HD-15 Buchse
Max. Bildschirmauflösung	1920 x 1440 bei 60 Hz
Bildwiederhohlfrequenz	250 MHz
Max. Kabellänge zwischen Monitor und Video Booster	65 m (213”) Max.
Signal Type	VGA, SVGA, XGA, Multisync
Netzteil	8VAC 300mA / 16VAC 300mA
Gewicht	80 g
Abmessungen (LxBxH)	97x56x26 mm

149125 / DC VS811 Video Booster

VIDEO BOOSTER

Through the video booster, you could extend the PC’s monitor to further extent, it is available to elongate the distance for one PC opposite monitor or video splitter opposite monitor.

- 250 MHz video bandwidth.
- Extends the video signal up to 65 meter. Supports the DDC, DDC2, DDC2B.
- Can be cascaded.
- The output is compatible with the VGA standard.

Video Input Connector	1 x HD-15 Male
Video Output Connector	1 x HD-15 Female
Max. Resolution	1920 x 1440 60 Hz
Pixel Frequency	250 MHz
Cable Distance (Device to Monitor)	65 m (213”) Max.
Signal Type	VGA, SVGA, XGA, Multisync
Power Adapter (Min.)	8VAC 300mA / 16VAC 300mA
Housing	Plastic
Weight	80 g
Dimensions (LxWxH) mm	97x56x26

149125 / DC VS811 Video Booster

©2003 All rights reserved